

KENWOOD

TK-7100H/8100H

VHF/UHF FM Transceivers

Fully equipped with a wide range of user-friendly features that incorporate famous Kenwood quality, the TK-7100H/8100H radios will improve your power of communication. These mobiles are convenient for any and all types of applications thanks to their compact body and durable chassis.

ALPHANUMERIC LCD DISPLAY

The brightly lit LCD display found on the TK-7100H/8100H offers user-friendly operation thanks to its 13-segment, 8-digit multi-capability alphanumeric display.



64 CHANNELS

The memory structure of the TK-7100H/8100H provides versatility and convenience by allowing up to 64 channels in 8 groups.

SCAN FUNCTIONS

Priority and group scan (single/multi) is available and allows channel(s) to be added and deleted.

TOUGH, COMPACT AND POWERFUL

Built to take rough treatment in stride, the TK-7100H/8100H meets the stringent MIL-STD 810 C/D/E/F standards for resistance to dust, vibration and shock. The "bath-tub" construction of



the chassis assures excellent heat dissipation characteristics, and installation is simplified thanks to the compact external dimensions — 6.30in (W) x 1.69in (H) x 5.39in (D). Furthermore, the discrete final MOS FET boasts powerful 45W (UHF) and 50W (VHF) output.

HIGH-QUALITY SPEAKER

The large-diameter oval (2.28in x 1.38in) speaker mounted in the front panel assures excellent clarity.

DTMF / MSK PTT ID

The TK-7100H/8100H features two PTT ID formats — DTMF (max. 16-digit DTMF code) and MSK (FleetSync™ format ID). PTT ID is a digital ANI (Automatic Number Identifier) that can be sent on each PTT, allowing clear identification of the person using the transceiver.

VERSATILE DTMF MODES

The TK-7100H/8100H can be set for the following DTMF encode and decode modes:

- **Code Squelch:** DTMF code squelch provides a 3 to 10 digit ID for DTMF paging.
- **Selective Call:** DTMF selective calling is a signalling function comprised of DTMF codes (ID code + Intermediate code + Status code) that allows direct radio calling even if the radio is left unattended. When the set ID and intermediate codes match, the radio's squelch will open and a numeric status code of up to 5-digits can be displayed.



- **Number display*:** When the DTMF code, such as the PTT ID number is received, it will display on the LCD.

* Does not operate while Code Squelch or Selective Call is activated.

OPERATOR SELECTABLE TONE (OST)

The user may change the QT/DQT signalling tones that are set with the FPU using the OST function. The FPU allows for these assignable tones to have an 8-digit name thus easing selection in the OST mode.

OTHER FEATURES

- Built-in QT/DQT Signalling
- SmarTrunk II™ OMNI capability (requires SmarTrunk board*)
- Data Ready (KDS-100, KGP-2A/2B, and 8 Programmable Function Port)
- Encryption Control Capability
- PC Programming**
- AVL capability (with KGP-2A/2B)
- Backlit keys for all buttons
- Ignition sense input
- 4-Programmable Keys
- Busy Channel Lockout
- Embedded Message
- Security features including Radio stun, Radio password, Data password, Embedded message, and Kenwood ESN
- Channel direct
- Time out Timer (TOT)
- Wide/narrow selection per channel

*SmarTrunk board is available from SmarTrunk Systems, Inc.

**Compatible with Windows 98/ME/2000/XP, English or Spanish version.



Options

■ **KMC-30**
Microphone (supplied)



■ **KMC-32**
16-key Keypad
Microphone



■ **KES-3**
External Speaker



■ **KLF-2**
Line Filter



■ **KPS-10A**
Regulated DC
Power Supply



■ **KPS-15**
DC Switching
Power Supply



■ **KMB-10**
Key Lock Adapter




■ **KMB-19**
Installation Kit



■ **KGP-2A**
GPS Receiver Modem
(requires KCT-39 option)



■ **KGP-2B**
GPS Controller Modem
(requires KCT-39 option)



■ **KDS-100**
Mobile Data Terminal
(requires KCT-39 option)



■ **KCT-18**
Ignition Sense Cable
(requires KCT-39 option)



■ **KCT-36**
3m Extension Cable
(for KCT-39)



■ **KCT-39**
Connection Cable



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

	TK-7100H	TK-8100H
GENERAL		
Frequency Range		
Type 1	146-174 MHz	450-490 MHz
Type 2	136-162 MHz	485-512 MHz
Type 3	-	400-430 MHz
Channels / Groups	64 CH / 8 GRP (Up to 64 channels can be allocated into 8 groups)	
Channel Spacing (Wide / Narrow)	25 kHz / 12.5 kHz	
PLL Channel Stepping	2.5 kHz, 5 kHz, 6.25 kHz, 7.5 kHz	5 kHz, 6.25 kHz
Operating Voltage	13.6 V, DC ±15%	
Current drain		
Standby		0.4 A
Receive		1.0 A
Transmit (High Power)		14.0 A
Operating Temperature Range	-22°F ~ +140°F (-30°C ~ +60°C)	
Frequency Stability (-22°F ~ +140°F)	±2.5 ppm	
Dimensions (W x H x D, without projections)	6-6/5 x 1-11/16 x 5-3/8 in. (160 mm x 43 mm x 137 mm)	
Weight (Body only, approximate)	2.6 lbs (1.18 kg)	
Antenna Impedance	50 Ω	
Channel Frequency Spread		
Type 1	28 MHz	40 MHz
Type 2	26 MHz	27 MHz
Type 3	-	30 MHz

	TK-7100H	TK-8100H
RECEIVER (Measurements made per EIA/TIA-603)		
Sensitivity (Wide / Narrow)	0.28μV / 0.35μV (12dB SINAD)	
Selectivity (Wide / Narrow)	75 dB / 65 dB	
Intermodulation Distortion (Wide / Narrow)	70 dB / 60 dB	
Spurious Response	75 dB	
Audio Output (4Ω, 5% Distortion)	4.0 W	
TRANSMITTER (Measurements made per EIA/TIA-603)		
RF Power Output (High / Low)	50W / 25W	45W / 25W
Spurious & Harmonics (High Power)	70 dB	
Modulation (Wide / Narrow)	16K0F3E / 11K0F3E	
FM Noise (Wide / Narrow)	45 dB / 40 dB	
Audio Distortion (Wide / Narrow)	Less than 3%	
Microphone Impedance	600Ω	

Kenwood reserves the right to change specifications and features without prior notice.
SmarTrunk II™ is a trademark of SmarTrunk Systems, Inc.
FleetSync™ is a trademark of Kenwood Corporation.

Applicable MIL-STD

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I Cat. 8	514.4/Procedure I Cat. 8	514.5/Procedure I Cat. 20
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.4/Procedure I

KENWOOD CORPORATION

2967-3, Ishikawa-machi, Hachioji-shi, Tokyo, 192-8525 Japan

KENWOOD U.S.A. CORPORATION

Communications Division

Division Headquarters

3975 Johns Creek Court, Suwanee, GA 30024-1265

Order Administration/Customer Support/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745



JQA-1205 091-A
ISO9001 Registered
Communications Equipment Division
Kenwood Corporation
ISO9001 certification